

IFW11

Ex d IIC T6



Features

- Fire & Ignition proof.
- Soft and comfortable light to relieve the fatigue of eyes.
- Excellent CRI for actual colour reproduction.
- Energy saving efficiency and low heat produce.
- AL die-cast housing for excellent heat management.
- Quick installation, special design,
- Highly reliable professional design.

Applications

- Chemical Industry, Paint Industry,
- Fertilizer Industry, Oil & Gas Industry,
- LPG Bottling Industry, Pharma Industry,
- Steel Industry, Cement Industry, Mines
- Refineries & Petrochemicals.



Characteristics

Optics

- Borosilicate Diffused Glass
- High transmission 93%
- Non-Removable

Thermal Interface Material

- High thermal conductivity
- Excellent heat transfer

Heat sink

- Aluminium - powder coated
- Excellent thermal conductivity

LED Driver

- Rated Supply: 240V AC, 50/60Hz
- PF > 0.95, THD < 10%,
- Short circuit, open circuit,
- O/V, U/V protection

Standards Compliance

- IS/IEC 60079-1 : 2014
- Cat. No.: ILS/WG/1231
- IS 15885 (Part 2/Sec 13)

Mounting

- Pendant – Eye Bolt (Default)
- Pendant – U- Clamp (Optional)

Installation

- Easy installation

Weight

- 4.0 Kg

Cable Entry

- M20 2 Nos.



20W / 30W / 45W



100 lm/W



6500K / 5000K / 3000K



>70



Diffused – Wide >160°



140-270V AC, 50Hz



Fulham / ILS



In-Built, Surge DM 4Kv CM 6Kv



Non dimmable



COB, Citizen / Bridgelux , SDCM <3



Ta: -10°C to 45°C





Lifespan >50000h @ L70 B50

Housing Color



Powder Coated – Light Grey Glossy (RAL631)

Distribution Curve



Product Code



Product Code	System Power (W)	System Lumen (Lm)	CRI (Ra)	Color Temp (CCT)	Body Color	Beam Angle	Diming	Weight (Kg)
IFW11-020CE765GDNXX	20	2000	70	6500K	Grey	Diffused	Non-Dim	4.0
IFW11-030CE765GDNXX	30	3000	70	6500K	Grey	Diffused	Non-Dim	4.0
IFW11-045CE765GDNXX	45	4500	70	6500K	Grey	Diffused	Non-Dim	4.0

Custom Order



Accessories



U Clamp Option

Use U in place of E

IFW11-045CE865GDDXX

