

IFA10

Ex d IIC T6



Characteristics

Enclosure

- Aluminium LM-6 - powder coated

Standards Compliance

- IS/IEC 60079-1 : 2014
- IS/IEC 60079-0 : 2011
- IS/IEC 60529 : 2001
- Cat. No.: ILS/WG/1231

Cable Entry

- M20 x 1.5 Pitch – 2 Nos.

Mounting

- Surface / Structure

Applicable Use

- Zone 1 & Zone 2
- Gas group IIA, IIB, IIC,
- Temperature class T6

Installation

- Easy installation

Weight

- 3.5 Kg

Features

- Fire & Ignition proof.
- AL die-cast LM-6 housing.
- Two earthing for better safety-internal & external.
- Neoprene gasket for trouble free long life.
- External hardware made of SS.
- Highly reliable professional design.
- Blinking / Non-Blinking type

Description

- Toughened Clear Glass
- Surface or structure mountable
- Finish – Epoxy Powder Coated
- Internal Wiring – PVC wiring with interwell brass bush

Applications

- Chemical, paint, fertilizer industries,
- Oil & gas, refinery, petrochemicals,
- LPG bottling, pharmaceutical
- Steel, Cement industries, Mines



10W



Red Color LEDs 760nm



240V AC, 50HZ



Ta: -10°C to 45°C

Housing Color



Powder Coated – Grey (RAL 7021)



Product Code

Product Code	Wattage (W)	Input Voltage (V)	LEDs	Mounting	Weight (Kg)
IFA10-010DPREDGCNXX	10W	240AC	DIP LED – RED Color-760nm, Non-Blink	U Bracket	3.5
IFA10-010DBREDGCNXX	10W	240AC	DIP LED – RED Color-760nm, Blinking	U Bracket	3.5

Custom Order



Accessories

Optional at Extra Cost

- Double Compression Cable Gland Brass/SS – M20x1.5 Pitch
- Stopper Plug Brass/SS/MS – M20x1.5 Pitch

